

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method of cooling a semiconductor chip, comprising:
providing a number of electrical devices on a semiconductor layer of ~~the semiconductor chip~~ a flip-chip configuration semiconductor chip;
integrally forming a substantially planar heat conducting layer on a backside surface of the semiconductor chip ~~with the semiconductor layer~~, wherein the heat conducting layer is compatible with semiconductor processing techniques, ~~the heat conducting layer being adjacent to the number of electrical devices~~, the heat conducting layer having a higher thermal conductivity than the semiconductor layer;
conducting heat generated by the number of electrical devices into the heat conducting layer; and
transmitting the heat generated by the number of electrical devices through the heat conducting layer from a first region having a first temperature to a second region having a second temperature that is lower than the first region[.]; and
transmitting heat through a substantially continuous interface between the heat conducting layer and an external heat sink.
2. (Original) The method of claim 1, wherein providing a number of electrical devices includes providing a number of transistors.
3. (Original) The method of claim 1, wherein coupling a heat conducting layer to the semiconductor layer comprises coupling a carbon containing layer to the semiconductor layer.
4. (Original) The method of claim 3 wherein coupling a carbon containing layer to the semiconductor layer comprises coupling a diamond containing layer to the semiconductor layer.
5. (Cancelled)

6. (Currently Amended) A method of cooling a semiconductor chip formed from a semiconducting material, comprising:

integrally coupling a substantially planar heat conducting layer to ~~the semiconductor chip~~ a back side surface of a flip-chip configuration semiconductor chip, wherein the heat conducting layer is compatible with semiconductor processing techniques, the heat conducting layer having a higher thermal conductivity than the semiconducting material;

conducting heat from the semiconductor chip into the heat conducting layer; ~~and~~ transmitting the heat through the heat conducting layer from a first region having a first temperature to a second region having a second temperature that is lower than the first temperature[.]; and

transmitting heat through a substantially continuous interface between the heat conducting layer and an external heat sink.

7. (Original) The method of claim 6, wherein coupling a substantially planar heat conducting layer to the semiconductor chip includes coupling a carbon containing layer to the semiconductor chip.

8. (Original) The method of claim 7, wherein coupling a carbon containing layer to the semiconductor chip includes coupling a diamond containing layer to the semiconductor chip.

9. (Cancelled)

10. (Currently Amended) A method of cooling a semiconductor chip, comprising:

integrally forming a diamond containing layer on a backside of a flip-chip configuration semiconductor chip, the chip including adjacent to a number of electrical devices ~~on a semiconductor layer~~;

conducting heat generated by at least a portion of the number of electrical devices in a first area into the ~~heat conducting~~ diamond containing layer; ~~and~~

spreading the heat generated by the electrical devices in the first area through the ~~heat~~
~~conducting diamond containing~~ layer to a larger second area wherein heat per unit area is
reduced[.]; and

transmitting heat through a substantially continuous interface between the diamond
containing layer and an external heat sink.

11. (Original) The method of claim 10, wherein integrally forming a diamond containing layer adjacent to a number of electrical devices includes integrally forming a diamond containing layer adjacent to a number of transistors.

12. - 13. (Cancelled)

14. (Currently Amended) The method of claim 10, wherein integrally forming a diamond containing layer adjacent to a number of electrical devices includes ~~integrally forming~~ chemical vapor depositing a diamond containing layer on a back side of the semiconductor ~~processor~~ chip.

15. (Cancelled)

16. (Currently Amended) A method of manufacturing a semiconductor chip, comprising:
fabricating a semiconductor layer in a flip-chip configuration semiconductor chip;
forming a number of electrical devices on the semiconductor layer;
electrically connecting the number of electrical devices; ~~and~~
integrally forming a substantially planar heat conducting layer on a backside surface of
the flip-chip configuration semiconductor chip ~~operatively connected to the semiconductor layer~~,
wherein the heat conducting layer is compatible with semiconductor processing techniques, ~~the~~
~~heat conducting layer being adjacent to the number of electrical devices~~, the heat conducting
layer having a higher thermal conductivity than the semiconductor layer[.]; and
coupling an external heat sink to the heat conducting layer to form a substantially
continuous interface.

17. (Original) The method of claim 16, wherein fabricating a semiconductor layer includes fabricating a silicon substrate.

18. (Original) The method of claim 16, wherein forming a substantially planar heat conducting layer includes forming a carbon containing layer.

19. (Original) The method of claim 18, wherein forming a carbon containing layer includes forming a diamond containing layer.

20. (Original) The method of claim 19, wherein forming a diamond containing layer includes chemical vapor deposition (CVD) depositing a diamond layer.

21. (Currently Amended) A method of manufacturing a semiconductor chip, comprising:
forming a number of transistors on a semiconductor layer in a flip-chip configuration semiconductor chip;
electrically connecting the number of transistors; and
integrally forming a substantially planar diamond containing layer on a backside surface of the flip-chip configuration semiconductor chip ~~operatively connected to the semiconductor layer~~, and adjacent to the number of transistors[.]; and
coupling an external heat sink to the diamond containing layer to form a substantially continuous interface.

22. (Original) The method of claim 21, wherein forming a number of transistors on a semiconductor layer includes forming a number of transistors on a silicon substrate.

23. (Cancelled)

24. (Currently Amended) The method of claim 21, wherein integrally forming a substantially planar diamond containing layer ~~operatively connected to the semiconductor layer, and adjacent~~

~~to the number of transistors~~ includes chemical vapor depositing integrally forming a substantially planar diamond containing layer ~~on a back side of the semiconductor chip.~~

25. (Cancelled)

26. (Currently Amended) A method of forming an electronic system, comprising:

forming a flip-chip processor chip, including:

forming a number of transistors on a semiconductor layer;

electrically connecting the number of transistors;

integrally forming a substantially planar diamond containing layer on a backside surface of the flip-chip processor chip; ~~operatively connected to the semiconductor layer, and adjacent to the number of transistors; and~~

coupling an external heat sink to the diamond containing layer to form a substantially continuous interface; and

coupling the flip-chip processor chip to a random access memory.

27. (Original) The method of claim 26, wherein forming a substantially planar diamond containing layer includes chemical vapor deposition (CVD) depositing a diamond layer.